

## Product data sheet

### Characteristics

# 1025-PT

Double switched socket outlet, Clipsal Solis T Series, horizontal, 10A, platinum



### Main

|                           |                        |
|---------------------------|------------------------|
| Range                     | Clipsal Solis T Series |
| Product or component type | Switched socket        |
| Product brand             | Clipsal                |
| Assembly Type             | Complete product       |
| Colour tint               | Platinum               |
| Protection                | Shuttered              |
| Main colour tint          | Platinum               |

### Complementary

|                                |                                                                                  |
|--------------------------------|----------------------------------------------------------------------------------|
| Control type                   | Rocker                                                                           |
| Number Of Outlets              | 2                                                                                |
| Socket-outlet type             | Double socket-outlet                                                             |
| Mounting Type                  | Screw                                                                            |
| Installation Type              | Flush                                                                            |
| Installation Orientation       | Horizontal                                                                       |
| Material                       | Aluminium                                                                        |
| Surface finish                 | Metallic                                                                         |
| [Ue] rated operational voltage | 230/240 V AC                                                                     |
| Network frequency              | 50 Hz                                                                            |
| [In] rated current             | 10 A                                                                             |
| Connections - terminals        | 4 x 2.5 mm <sup>2</sup> screw terminals<br>3 x 4 mm <sup>2</sup> screw terminals |
| Embedding depth                | 23.5 mm                                                                          |
| Depth                          | 27.4 mm                                                                          |
| Height                         | 74 mm                                                                            |
| Width                          | 148 mm                                                                           |
| Mounting Centers               | 84 mm                                                                            |
| Cut-out dimensions             | 93 x 50 mm                                                                       |
| Surface treatment              | Painted                                                                          |
| Screwdriver shape              | Philips No 2<br>Square drive no 1 (SQ1)                                          |
| Wire stripping length          | 16 mm                                                                            |
| Number of power socket outlets | 2 x 2P + E, Australian/New Zealand                                               |
| Cover Thickness                | 5 mm                                                                             |
| Number Of Switches             | 2                                                                                |

### Environment

|                                       |             |
|---------------------------------------|-------------|
| Product certifications                | RCM         |
| Standards                             | AS/NZS 3112 |
| Relative humidity                     | 10...95 %   |
| Ambient air temperature for operation | 0...45 °C   |

## Packing Units

|                              |     |
|------------------------------|-----|
| Unit Type of Package 1       | PCE |
| Number of Units in Package 1 | 1   |

## Offer Sustainability

|                            |                                                                                                                                 |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| REACH Regulation           | <a href="#"> REACH Declaration</a>             |
| REACH free of SVHC         | Yes                                                                                                                             |
| EU RoHS Directive          | Compliant <a href="#"> EU RoHS Declaration</a> |
| Toxic heavy metal free     | Yes                                                                                                                             |
| Mercury free               | Yes                                                                                                                             |
| China RoHS Regulation      | <a href="#"> China RoHS Declaration</a>        |
| RoHS exemption information | <a href="#"> Yes</a>                           |