


Product data sheet

Characteristics

1025USBC-ZB

Double switched socket + USB charger, Clipsal Solis, horizontal, USB C type, 10A, matt black



Main

Product or component type	Switched socket with USB charger
Assembly Type	Complete product
Standards	AS/NZS 3112
Product certifications	RCM
Main colour tint	Matt black

Complementary

Range	Clipsal Solis
Number Of Outlets	2
Device mounting	Wall mounted 65 mm
Cover type	With shutter
Number of power socket outlets	2 x 2P + E, Australian/New Zealand
Rated current	10 A 230/240 V, AC, 50 Hz
Connections - terminals	4 x 2.5 mm ² screw terminals 3 x 4 mm ² screw terminals
Colour tint	Matt black
Surface finish	Matt
Surface treatment	Painted
Additional Function	USB type C
Material	Plastic
Screwdriver shape	Philips No 2 Square drive no 1 (SQ1)
Wire stripping length	16 mm
Fixing mode	By screw
Fixing center	120 mm
Height	74 mm
Width	148 mm
Depth	69.5 mm
Sale per indivisible quantity	1
Installation Type	Flush
Installation Orientation	Horizontal
Control type	Rocker
Cover Thickness	4.5 mm
Cut-out dimensions	130 x 50 mm
Number Of Switches	2

Environment

Ambient air temperature for operation	0...45 °C
Relative humidity	10...95 %

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Offer Sustainability

REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes