



Main

| | |
|---------------------------|-----------|
| Range | 56 Series |
| Product or component type | Plug |

Complementary

| | |
|---------------------------------------|------------------------|
| Rated current | 32 A |
| [Ue] rated operational voltage | 250 V |
| Material | Plastic |
| Colour tint | Orange |
| Surface finish | Gloss |
| Network frequency | 50 Hz |
| Network number of phases | 1 phase |
| Pin number | 3 |
| Ambient air temperature for operation | -40...55 °C |
| Cable cross section | 9...29 mm ² |
| Quantity per set | Set of 4 |
| Type of packing | Carton |

Environment

| | |
|-------------------------|------|
| IP degree of protection | IP66 |
|-------------------------|------|

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 391.0 g |
| Package 1 Height | 19.6 cm |
| Package 1 Width | 9 cm |
| Package 1 Length | 9 cm |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

China RoHS Regulation

 [China RoHS Declaration](#)

Environmental Disclosure

 [Product Environmental Profile](#)
