



Main

| | |
|---------------------------|--------------------------------|
| Range of product | 56 Series™ |
| Product or component type | Residual current device switch |
| Control type | Push-button |

Complementary

| | |
|---------------------------------------|-----------------|
| Material | Plastic |
| Colour tint | Grey |
| Surface finish | Gloss |
| Installation direction | Vertical |
| Width | 95 mm |
| Height | 191 mm |
| Rated current | 20 A |
| [Ue] rated operational voltage | 230/240 V |
| Network frequency | 50 Hz |
| Network number of phases | 1 phase |
| Number of gangs | 1 gang |
| Pin number | 3 |
| Device composition | Round pin |
| Mounting mode | Surface mounted |
| Fixing center | 84 x 84 mm |
| IP degree of protection | IP66 |
| Ambient air temperature for operation | -10...40 °C |
| Quantity per set | Set of 4 |
| Type of packing | Carton |

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 0.254 kg |
| Package 1 Height | 6 cm |
| Package 1 Width | 9.5 cm |
| Package 1 Length | 9.5 cm |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |