



Main

| | |
|---------------------------|---------------|
| Range of product | 56 Series™ |
| Range | 56 Series |
| Product brand | Clipsal |
| Product or component type | Rotary switch |
| Device application | Control |
| Colour tint | Grey |
| Motor M-rating AS3133 | M50 |
| Quantity per set | Set of 4 |
| Type of packing | Carton |

Complementary

| | |
|--------------------------------|--------------------------|
| Number of poles | 1 |
| Control type | Rotary |
| Material | PC (polycarbonate) |
| Surface finish | Gloss |
| Installation direction | Vertical |
| Width | 95 mm |
| Height | 95 mm |
| Depth | 62 mm |
| Rated current | 10A/10AX |
| [Ue] rated operational voltage | 240 V |
| Network frequency | 50 Hz |
| Network number of phases | 1 phase |
| Number of gangs | 1 gang |
| Mounting mode | Surface mounted |
| Fixing center | 84 x 84 mm |
| Cable cross section | 0.75...6 mm ² |

Environment

| | |
|---------------------------------------|-------------|
| IP degree of protection | IP66 |
| Ambient air temperature for operation | -40...55 °C |

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 0.156 kg |
| Package 1 Height | 6 cm |
| Package 1 Width | 9.5 cm |
| Package 1 Length | 9.5 cm |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |