# Product data sheet

Specifications



## Switched Socket, Iconic, 2 switch & 2 socket, vertical, 10A, 230/240V, silver shadow

PDLS392-SH

## Main

| | |
|---|---|
| **Range of product** | Iconic |
| **Range** | Iconic |
| **Product or component type** | Switched socket |
| **Device presentation** | Complete product |
| **Product brand** | PDL |
| **Outlet poles configuration** | 2P + E with shutter |
| **Outlet standard** | Australian |
| **Colour tint** | Silver shadow (SH) |
| **Main colour tint** | Silver shadow |
| **Switch application** | On/off switching |

## Complementary

| | |
|---|---|
| **Socket-outlet type** | Twin switched socket-outlet |
| **Device mounting** | Flush |
| **Mounting position** | Vertical |
| **Number of rocker** | 2 |
| **fixing mode** | By screws |
| **Installation direction** | Vertical |
| **Surface finish** | Glossy |
| **surface treatment** | Anodised |
| **Rated current** | 10 A at 230/240 V AC 50 Hz |
| **Connections - terminals** | screw terminals |
| **Clamping connection capacity** | 1 x 2.5...4 x 2.5 mm² for rigid cable(s)<br>1 x 2.5...4 x 2.5 mm² for stranded cable(s)<br>1 x 2.5...4 x 2.5 mm² for flexible cable(s) |
| **Wire stripping length** | 16 mm |
| **Material** | Metal |
| **Height** | 82 mm |
| **Width** | 126 mm |
| **Depth** | 36.5 mm |
| **Embedding depth** | 28 mm |
| **Network frequency** | 50 Hz |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---|---|
| **[Ue] rated operational voltage** | 230/240 V |
| **Rated current** | 10 A |
| **Network type** | AC |
| **Connections - terminals** | Screw terminals |
| **Socket number** | 2 |

## Packing Units

| | |
|---|---|
| **Unit Type of Package 1** | PCE |
| **Number of Units in Package 1** | 1 |
| **Package 1 Height** | 5.3 cm |
| **Package 1 Width** | 15 cm |
| **Package 1 Length** | 10.2 cm |
| **Package 1 Weight** | 173 g |
| **Unit Type of Package 2** | CAR |
| **Number of Units in Package 2** | 20 |
| **Package 2 Height** | 23 cm |
| **Package 2 Width** | 26.7 cm |
| **Package 2 Length** | 34.1 cm |
| **Package 2 Weight** | 3.76 kg |

## Contractual warranty

| | |
|---|---|
| **Warranty (in months)** | 18 |

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

### Environmental footprint

| | |
|---|---|
| Total lifecycle Carbon footprint | **11 kg CO2 eq.** |
| Carbon footprint of the manufacturing phase [A1 to A3] | **1 kg CO2 eq.** |
| Carbon footprint of the distribution phase [A4] | **0 kg CO2 eq.** |
| Carbon footprint of the installation phase [A5] | **0 kg CO2 eq.** |
| Carbon footprint of the use phase [B2, B3, B4, B6] | **9 kg CO2 eq.** |
| Carbon footprint of the end-of-life phase [C1 to C4] | **0.3 kg CO2 eq.** |
| Environmental Disclosure | **Product Environmental Profile** |

## Use Better

### Materials and Substances

| | |
|---|---|
| Packaging made with recycled cardboard | **Yes** |
| Packaging without single use plastic | **No** |
| EU RoHS Directive | **Compliant** |
| REACh Regulation | **Reference contains Substances of Very High Concern above the threshold** |
| Halogen-free status | **Halogen free product** |
| PVC free | **No** |

## Use Again

### Repack and remanufacture

| | |
|---|---|
| Recyclability potential, in % | **43** |
| End of life manual availability | **No need of specific recycling operations** |
| Take-back | **No** |

Image of product / Alternate images

**Alternative**













